



ADVANTA® TRAILER TIRES LIMITED WARRANTY

US AUTOFORCE ADVANTA ST RADIAL LIMITED WARRANTY

American Pacific Industries, Inc. (API) hereby warrants that every new Advanta ST Trailer Tire as distributed through US AutoForce bearing the brand name Advanta to be free from conditions of workmanship and material that would cause the tire to become unserviceable for the life of the original tread less 2/32". The life of the original usable tread ends when the tire tread has worn down to 2/32" remaining, at which point the tire is considered to be fully worn out. This warranty applies only to the original purchaser for a period of three (3) years from the date of manufacture. API's liability under this warranty shall be limited to replacement and/or credit for the cost of the tire.

GENERAL WARRANTY AND WARRANTY OBLIGATION

If any Advanta tire becomes unserviceable, API will do either of the following:

- A. If the tire becomes unserviceable due to material or workmanship during the first 2/32" of the original tread, API will replace such tire with a comparable new Advanta tire free of charge. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.
- B. If the tire becomes unserviceable due to material or workmanship after the first 2/32" of tread wear, a credit will be given toward the purchase of a comparable new tire in proportion to the usable tread remaining. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.

Adjustment for out-of-balance or out-of-round tires is not covered by this warranty.

EXCLUSIONS

- A. All API warranties are limited to the original purchaser and the original vehicle on which they are mounted and are not assignable to subsequent purchasers or vehicles.
- B. This limited warranty is applicable only in the United States, Canada or Mexico and any tire used on a vehicle registered or operated outside of these areas is not covered by this warranty.
- C. The following is not covered by the Limited Warranty:
 - 1. Tires branded or marked "Non-Adjustable" (N/A) or "Blemished (Blem), or previously adjusted.
 - 2. Tires that are deemed out-of-round or out-of-balance
 - 3. Failure, damage or irregular wear due to:
 - a. Road hazards (i.e. puncture, cut, snag, impact breaks, etc.);
 - b. Fire, accident or vandalism;
 - c. Mechanical condition of vehicle, including improper alignment, improper inflation, wheel imbalance, faulty shocks or brakes;
 - d. Misapplication of the tire, use of improper inner tube;
 - e. Alteration of the tire or addition of foreign material or transfer from one vehicle to another;
 - 4. Cost of service, mounting and dismounting.
 - 5. Loss of time or use, inconvenience, or any incidental or consequential damages of any type or nature.

OWNER'S OBLIGATIONS

In order to be eligible for Limited Warranty Service, the owner must:

- A. Present the tire to an authorized dealer;
- B. Present proof of purchase to the satisfaction of the dealer;
- C. Complete and sign an API Warranty Claim Form, which is available from any authorized dealer; and
- D. Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges or cost of other services ordered.

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of API tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.



24/7 Online Order
usautoforce.com



Phone
800.490.4901



Fax
800.688.3099

Advanta ST - US AutoForce - May 2016

ADVANTA®

HIGH SPEED TRAILER TIRES



PERFORMANCE GUARANTEED®

ECOSAFE



ADVANTA®

HIGH SPEED TRAILER TIRES

Quality speaks for itself®

Experience the difference®

- Steel belted construction for added strength and stability
- Advanced tread compound designed to improve fuel economy and resist weather cracking.

PRODUCT CODE	TIRE SIZE	PLY	LOAD INDEX (SINGLE/ DUAL)	SPEED SYMBOL	OVERALL DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32 ND)	LOAD CAPACITY (LBS) SINGLE/ DUAL
ADVANTA RADIAL ST								
1952001831	ST175/80R13	6	91/87	M	24.0	7.0	9	1360/1200
1952002041	ST205/75R14	6	100/96	M	26.1	8.0	9	1760/1570
1952002141	ST215/75R14	6	102/98	M	26.7	8.5	9	1870/1650
1952002051	ST205/75R15	6	101/97	M	27.1	8.0	9	1820/1610
1952002052	ST205/75R15	8	107/102	M	27.1	8.0	9	2150/1870
1952002252	ST225/75R15	8	113/108	M	28.3	9.2	9	2540/2200
1952002253	ST225/75R15	10	117/112	M	28.3	9.2	9	2830/2470
1952002262	ST225/90R16	14	122/118	M	31.8	8.7	10	3300/2910
1952002863	ST235/80R16	10	124/120	M	30.8	9.3	10	3520/3080
1952003864	ST235/85R16	12	128/124	M	31.7	9.3	10	3960/3520
1952003865	ST235/85R16	14	129/125	M	31.7	9.3	10	4080/3640

ECOSAFE



ADVANTA RADIAL ST